

Applications:
Round flexible loudspeaker cables with double density sheath, suitable for speakon, banana and other audio connectors.

Characteristics:
Conductors: O.F.C. red copper
Cond. Insulation: PVC
Core colours: Black, Red
I° Sheath: White soft PVC
II° Sheath: PVC
Total sheath colours: **Black, Grey-pale blue**



tasker® Code	Cond. number	Nominal section mm²	Cond. Format. mm.	External core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C265	2	2 x 1,00 (17 AWG)	32x0,20	2,6	7,2	100	B	8,0
C275		2 x 1,50 (16 AWG)	48x0,20	3,0	8,0	100	B	10,0
C266		2 x 2,00 (14 AWG)	64x0,20	3,4	8,8	100	B	11,5
C276		2 x 2,50 (13 AWG)	80x0,20	3,5	9,0	100	B	13,0
C267		2 x 3,00 (12 AWG)	96x0,20	3,9	9,8	100	B	14,5
C277		2 x 4,00 (11 AWG)	128x0,20	4,2	10,8	50	B	8,0

Applications:
Round flexible loudspeaker cables suitable for speakon, banana and other audio connectors.

Characteristics:
Conductors: O.F.C. red copper
Cond. Insulation: PVC
Core colours: Black, Red, Light-blue, Green, Yellow, Grey, Brown, Bright-orange
Sheath: PVC
Sheath colours: **Black, Grey-pale blue**



tasker® Code	Cond. number	Nominal section mm²	Cond. Format. mm.	External core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C268	2+2	2 x 1,50 + 2 x 2,50	48x0,20 80x0,20	3,0 3,5	10,0	100	B	18,0
C288	4	4 x 2,50	80x0,20	3,5	10,8	100	B	23,0
C279		4 x 4,00	128x0,20	4,2	13,0	100	B	36,0
C269	8	8 x 2,50	80x0,20	3,5	14,0	50	B	27,0
C289		4 x 2,50 + 4 x 4,00	80x0,20 128x0,20	3,5 4,2	16,5	100	B	48,0

Conductor Resistance Ω/Km ± 5%	Max rated Voltage AC - V	Operative Temperature °C
16 12	49	-15 / +70
12	49	-15 / +70
6	49	-15 / +70
12	49	-15 / +70
12 6	49	-15 / +70