

# 12FW64

---

LF Drivers - 12.0 Inches





- 500 W continuous program power capacity
- 64 mm (2.5 in) aluminium voice coil
- 50 - 3000 Hz response
- 98 dB sensitivity



# 12FW64

## LF Drivers- 12.0 Inches



### SPECIFICATIONS

Nominal diameter	320 mm (12.0 in)
Nominal impedance	8 Ω
Minimum impedance	6.7 Ω
Nominal power handling <sup>1</sup>	250 W
Continuous power handling <sup>2</sup>	500 W
Sensitivity (1W/1m) <sup>3</sup>	98.0 dB
Frequency range	55 - 3000 Hz
Voice coil diameter	64 mm (2.5 in)
Winding material	Aluminium
Former material	Glass Fibre
Winding depth	14 mm (0.55 in)
Magnetic gap depth	8 mm (0.31 in)
Flux density	1.3 T

### DESIGN

Surround shape	Double Roll
Cone shape	Exponential
Magnet material	Ferrite
Spider	Single
Pole design	T-Pole
Woofers cone treatment	WP Waterproof Front Side
Recommended enclosure	40.0 dm <sup>3</sup> (1.4 ft <sup>3</sup> )
Recommended tuning	55 Hz

### PARAMETERS

F <sub>s</sub>	55 Hz
R <sub>e</sub>	5.2 Ω
Q <sub>es</sub>	0.32
Q <sub>ms</sub>	3.5
Q <sub>ts</sub>	0.29
V <sub>as</sub>	64.0 dm <sup>3</sup> (2.26 ft <sup>3</sup> )
S <sub>d</sub>	522.0 cm <sup>2</sup> (80.9 in <sup>2</sup> )
η <sub>o</sub>	3.6 %
X <sub>max</sub>	5.0 mm
X <sub>var</sub>	5.0 mm
M <sub>ms</sub>	47 g
Bl	15.5 Txm
Le	1.0 mH
EBP	171 Hz

### MOUNTING AND SHIPPING INFO

Overall diameter	315 mm (12.4 in)
Bolt circle diameter	298 mm (11.7 in)
Baffle cutout diameter	283.0 mm (11.1 in)
Depth	136 mm (5.35 in)
Flange and gasket thickness	13 mm (0.51 in)
Air volume occupied by driver	3.0 dm <sup>3</sup> (0.1 ft <sup>3</sup> )
Net weight	5.6 kg (12.3 lb)
Shipping weight	6.2 kg (13.7 lb)
Shipping box	340x340x170 mm (13.4x13.4x6.7 in)

### SERVICE KIT

RCK12FW648

1. 2 hours test made with continuous pink noise signal (6 dB crest factor) within the range F<sub>s</sub>-10F<sub>s</sub>. Power calculated on rated minimum impedance. Loudspeaker in free air.
2. Power on Continuous Program is defined as 3 dB greater than the Nominal rating.
3. Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.