



WGX800

Line Array Sources - 1.4 Inches

Line Array optimized Waveguide with DE800 driver
 120° max horizontal coverage
 220 W continuous program power capacity
 75 mm (3 in) aluminium voice coil
 Composite Polyimide/Titanium diaphragm
 500 - 17000 Hz response
 108 dB sensitivity
 Neodymium magnet assembly with shorting copper cap

Specifications

Horizontal coverage	120 ° Max
Active radiating factor	93.7 %
Recommended crossover ¹	0.8 kHz
Waveguide material	Cast Aluminium
Nominal impedance	8 Ω
Minimum impedance	8.6 Ω
Nominal power handling ²	110 W
Continuous power handling ³	220 W
Sensitivity (1W/1m) ⁴	108.0 dB
Frequency range ⁵	1 - 17 kHz
Voice coil diameter	75 mm (3.0 in)
Winding material	Aluminium
Diaphragm material	Composite Polyimide/Titanium
Flux density	1.85 T
Magnet material	Neodymium Ring

Mounting And Shipping Info

Driver diameter	124 mm (4.9 in)
Dimensions	163x130x235 mm (6.4x5.1x9.3 in)
Net weight	3.3 kg (7.3 lb)
Shipping units	1
Shipping weight	3.4 kg (7.5 lb)
Shipping box	245x140x175 mm (9.6x5.5x6.9 in)

Mounting And Shipping Info

Waveguide baffle cutout	153x25 mm (6x1 in)
-------------------------	--------------------

1. 12 dB/oct. Or higher slope high-pass filter.

4. Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.

2. 2 hour test made with continuous pink noise signal (6 dB crest factor). Power calculated on rated minimum impedance.
5. Waveguide mounted on 90°x10° bell horn
3. Power on Continuous Program is defined as 3 dB greater than the Nominal rating.

