



DE1080TN

HF Drivers Neo - 1.5 Inches

280 W continuous program power capacity
1.5" horn throat diameter
100 mm (4 in) CCAW voice coil
Titanium diaphragm
500 - 20000 Hz response
109 dB sensitivity
Neodymium magnet assembly with shorting copper cap

Specifications

Throat diameter	38 mm (1.5 in)
Nominal impedance	8 Ω
Minimum impedance	8.4 Ω
Nominal power handling	140 W
Continuous power handling	280 W
Sensitivity (1W/1m)	109.0 dB
Frequency range	1 - 20 kHz
Recommended crossover	1.0 kHz
Voice coil diameter	100 mm (4.0 in)
Winding material	Aluminium
Inductance	0.18 mH
Diaphragm material	Titanium
Flux density	1.95 T
Magnet material	Neodymium Ring

Mounting And Shipping Info

Net weight	3.4 kg (7.5 lb)
Shipping units	1
Shipping weight	3.7 kg (8.1 lb)
Shipping box	195x195x100 mm (7.7x7.7x3.9 in)

Other

Replacement diaphragm	MMD4BTN8M
-----------------------	-----------

Mounting And Shipping Info

Overall diameter	154 mm (6.1 in)
Depth	60 mm (2.4 in)