





## DE250TN HF Drivers FE - 1.0 Inches

120 W continuous program power capacity 1" horn throat diameter 44 mm (1.7 in) aluminium voice coil Titanium diaphragm 1000 - 18000 Hz response 106 dB sensitivity

| Specifica | tions |
|-----------|-------|
|-----------|-------|

| Throat diameter           | 25 mm (1.0 in) |
|---------------------------|----------------|
| Nominal impendance        | 8 Ω            |
| Minimum impendance        | 7.4 Ω          |
| Nominal power handling    | 60 W           |
| Continuous power handling | 120 W          |
| Sensitivity (1W/1m)       | 106.0 dB       |
| Frequency range           | 1 - 18 kHz     |
| Recommended crossover     | 1.5 kHz        |
| Voice coil diameter       | 44 mm (1.7 in) |
| Winding material          | Aluminium      |
| Inductance                | 0.11 mH        |
| Diaphragm material        | Titanium       |
| Flux density              | 1.85 T         |
| Magnet material           | Ceramic        |

## Mounting And Shipping Info

| Overall diameter | 120 mm (4.7 in) |
|------------------|-----------------|
| Depth            | 62 mm (2.4 in)  |

## Mounting And Shipping Info

| · · · · · · · · · · · · · · · · · · · |                                      |
|---------------------------------------|--------------------------------------|
| Net weight                            | 2.1 kg (4.6 lb)                      |
| Shipping units                        | 8                                    |
| Shipping weight                       | 17.5 kg (38.5 lb)                    |
| Shipping box                          | 260x260x190 mm<br>(10.2x10.2x7.5 in) |

## Other

Replacement MMDDE250TN8M diaphragm