



# DE602

## HF Drivers FE - 1.4 Inches

160 W continuous program power capacity  
1.4" horn throat diameter  
65 mm (2.5 in) aluminium voice coil  
Titanium diaphragm  
1000 - 18000 Hz response  
108 dB sensitivity  
Shorting copper cap for extended HF response

### Specifications

Throat diameter	36 mm (1.4 in)
Nominal impedance	8 Ω
Minimum impedance	7.6 Ω
Nominal power handling	80 W
Continuous power handling	160 W
Sensitivity (1W/1m)	108.0 dB
Frequency range	1 - 18 kHz
Recommended crossover	1.2 kHz
Voice coil diameter	65 mm (2.5 in)
Winding material	Aluminium
Inductance	0.15 mH
Diaphragm material	Titanium
Flux density	1.55 T
Magnet material	Ceramic

### Mounting And Shipping Info

Net weight	3.4 kg (7.5 lb)
Shipping units	2
Shipping weight	7.5 kg (16.5 lb)
Shipping box	210x210x190 mm (8.3x8.3x7.5 in)

### Other

Replacement diaphragm	MMD6108
-----------------------	---------

### Mounting And Shipping Info

Overall diameter	145 mm (5.7 in)
Depth	65 mm (2.5 in)