



DCM50

HF Drivers - 2 Inches

160 W continuous program power capacity
2" horn throat diameter
400 – 10000 Hz response
108.5 dB sensitivity
Neodymium magnet assembly

Specification

| | |
|------------------------------|----------------|
| Throat Diameter | 50 mm (2 in) |
| Nominal Impedance | 8 ohm |
| Minimum Impedance | 8 ohm |
| Nominal Power Handling (AES) | 80 W |
| Continuous Power Handling | 160 W |
| Sensitivity (1W/1m) | 108.5 dB |
| Frequency Range | 0.4 - 10 Hz |
| Recommended Crossover | 0.4 kHz |
| Voice Coil Diameter | 51 mm (2 in) |
| Winding Material | Aluminium |
| Inductance | 0.18 mH |
| Diaphragm material | Composite |
| Flux Density | 2.1 T |
| Magnet Material | Neodymium Ring |

Mounting & Shipping

| | |
|-----------------|------------------------------------|
| Net Weight | 3.2 kg (7 lb) |
| Shipping Weight | 3.4 kg (7.5 lb) |
| Shipping Box | 170x170x140 mm (6.7x6.7x5.5 in) |

Replacement Diaphragm

Mounting & Shipping

| | |
|------------------|------------------|
| Overall Diameter | 152 mm (6 in) |
| Depth | 108 mm (4.25 in) |