



DE820TN

HF Drivers - 1.4 Inches

220 W continuous program power capacity
 1.4" horn throat diameter
 75 mm (3 in) aluminium voice coil
 Titanium diaphragm
 500 – 18000 Hz response
 107 dB sensitivity
 Neodymium magnet assembly with shorting copper cap

Specification

Throat Diameter	36 mm (1.4 in)
Nominal Impedance	8 ohm
Minimum Impedance	8.5 ohm
Nominal Power Handling (AES)	110 W
Continuous Power Handling	220 W
Sensitivity (1W/1m)	107 dB
Frequency Range	0.5 - 18 Hz
Recommended Crossover	1.2 kHz
Voice Coil Diameter	75 mm (3 in)
Winding Material	Aluminium
Inductance	0.14 mH
Diaphragm material	Titanium
Flux Density	1.85 T
Magnet Material	Neodymium Ring

Mounting & Shipping

Net Weight	2.3 kg (5.1 lb)
Shipping Weight (4 units)	9.8 kg (21.5 lb)
Shipping Box (4 units)	300x160x180 mm (11.8x6.3x7.5 in)

Replacement Diaphragm	MMD820TN
-----------------------	----------

Mounting & Shipping

Overall Diameter	124 mm (4.9 in)
Depth	55 mm (2.2 in)