

SPECIFICATIONS – SC LIVE 2

- **Bit Depth:** 24 bit (44.1kHz Sample Rate)
 - **Frequency Response:** 20Hz - 20kHz, +/- 0.5dB
 - **Dynamic Range:** > 110dB, 1kHz @ 0dBFS, A-Weighted
 - **Signal-to-Noise Ratio:** > 92 dB Max Out – Dynamic Range
 - **Channel Separation:** < 106dB, 1kHz @ 0dBFS (Crosstalk from L to R / R to L is -106dB, 1 kHz, unity)
 - **T.H.D.**
 - **Microphone:** < 0.0035%, 1kHz @0dBFS (1 kHz, unity)
-

- **Analog Input**
 - **Microphone:**
 - -40 dBV (unity)
 - -60 dBV (minimum)
-

- **Analog Output**
 - **Master, Balanced:**
 - +18 dBu (maximum)
 - **Master, Unbalanced:**
 - +15 dBu (maximum)
 - **Headphone Output:**
 - < 452mW @32ohms, 25mW @ 590 ohms
-

- **Speakers**
 - **Frequency Response:**
 - 20Hz - 20kHz, +/- 1dB
-

- **Network**
 - **Wi-Fi**
-

- **Connections**
 - (1) XLR outputs (main left/right, balanced)
 - (1) RCA output pair (main left/right, unbalanced)
 - (1) 1/4" (6.35mm) stereo output (headphones)
 - (1) 1/8" (3.5mm) stereo output (headphones)
 - (1) 1/4" (6.35mm) mic input
 - (2) USB 2.0 ports (for USB drives, Type A)
 - (1) USB port (to computer)
 - (1) SD card slot (SD, SDDHC, SDXC)
-

○ **Power**

- **Connection:** External power supply, DC, Center Positive, 12.0 V 3.0 A
 - **Input Voltage:** 100–240 VAC, 50/60 Hz
-

○ **Dimensions (Width x Depth x Height)**

- 26.7" x 15.4" x 3.9"
-

○ **Weight**

- 10.1 lbs.