

SPECIFICATIONS – SC LIVE 4

- **Bit Depth:** 24 bit (44.1kHz Sample Rate)
- **Frequency Response:** 20Hz - 20kHz, +/- 0.5dB
- **Dynamic Range:** > 110dB, 1kHz @ 0dBFS, A-Weighted
- **Signal-to-Noise Ratio:** > 92 dB Max Out – Dynamic Range
- **Channel Separation:** < 107dB, 1kHz @ 0dBFS (Crosstalk from Left to Right/Right to Left is -107dB, 1 kHz, unity)
- **T.H.D.**
 - **Microphone:** < 0.0033%, 1kHz @0dBFS (1 kHz, unity)
 - **Auxiliary:** < 0.0048%, 1kHz @0dBFS (1 kHz, unity)

-
- **Analog Input**
 - **Microphone:**
 - 110mVrms -60 dBu (minimum)
 - **Auxiliary:**
 - +15dBV (maximum)

-
- **Analog Output**
 - **Master, Balanced:**
 - +18 dBu (maximum)
 - **Master, Unbalanced:**
 - +15 dBu (maximum)
 - **Booth:**
 - +18 dBu (maximum)
 - **Headphone Output:**
 - < 452mW @32ohms, 25mW @ 590 ohms

-
- **Speakers**
 - **Frequency Response:**
 - 20Hz - 20kHz, +/- 1dB

-
- **Network**
 - **Wi-Fi**

-
- **Connections**
 - (1) XLR outputs (main left/right, balanced)
 - (1) RCA output pair (main left/right, unbalanced)
 - (1) 1/4" TRS booth output pair
 - (1) 1/4" (6.35mm) stereo output (headphones)
 - (1) 1/8" (3.5mm) stereo output (headphones)
 - (1) 1/4" (6.35mm) TRS mic input
 - (1) XLR & TRS Combo Jack (6.35mm) mic input
 - (1) RCA pair Aux input
 - (2) USB 2.0 ports (for USB drives, Type A)
 - (1) USB port (to computer)
 - (1) SD card slot (SD, SDDHC, SDXC)
-

○ **Power**

- **Connection:** External power supply, DC, Center Positive, 12.0 V 3.0 A
- **Input Voltage:** 100–240 VAC, 50/60 Hz

○ **Dimensions (Width x Depth x Height)**

- 28.3" x 15.9" x 3.9"

○ **Weight**

- 12.8 lbs.