



# PROTRON 3K™

SKU# **PRELIMINARY SPECIFICATIONS**

The Protron 3K™ is a new high powered LED strobe featuring (202) CREE™ 3W Cool White LEDs, 80,000 lumens, 120° beam angle, (2) power modes (HIGH or LOW), strobe effect macros including burst, pulse, lighting, and full ON\*, (2) silent cooling fans, electronic dimming, 3/5pin DMX and powerCON in/out connections, (4) button LCD control panel, an integrated rigging yoke, 900W max power consumption, and a multi-voltage universal auto switching power supply (100-240v). \*Thermally regulated output at full max 10 seconds.



## FEATURES

**(202) CREE™ 3W Cool White LEDs**

**80,000 Total Lumens**

**120° Beam Angle**

**(2) Power Modes (HIGH or LOW)**

**Electronic Dimming**

**Burst, Pulse, Lighting, Full ON\***

**(2) Silent Cooling Fans**

**\*Thermally regulated output at full max 10 seconds.**



**PRODUCT SPECIFICATIONS**

**FEATURES**

- 120° Beam Angle
- (2) Power Modes (HIGH and LOW)
- (2) Silent Cooling Fans

**SOURCE**

- (202) CREE™ 3W Cool White LEDs
- 80,000 Total Lumens
- 100,000 Average LED Life

**PHOTOMETRIC DATA**

16,450 LUX 1,528 FC @3.3' (1m) (120° Full ON)

**EFFECTS**

- Electronic Dimming
- Burst, Pulse, Lighting, Full ON\*

\*Thermally regulated output at full max 10 seconds.

**CONTROL / CONNECTIONS**

- 3 DMX Channel Modes (1 / 2 / 3 / 4)
- 4 Button Control Panel
- LCD Menu Display
- 3/5pin DMX In/Out
- powerCON In/Out
- Power Link Up To (2) Units at 120V

**SIZE / WEIGHT**

- Length: 21.5" (546mm)
- Width: 6.1" (154mm)
- Vertical Height: 11.7" (297mm)
- Weight: 14.0 lbs. (6.4kg)

**ELECTRICAL / THERMAL**

- AC 100-240V - 50/60Hz
- 900W Max Power Consumption
- Max Ambient Temperature 113°F (40°C)

**APPROVALS / RATINGS**

CE | IP20


**INSTALLATION**

- Rigging: Intergrated Yoke
- Working Position: Any (360°)

**INCLUDED ITEMS**


- (1) powerCON Cable

**PHOTOMETRIC DATA**



Distance	m		ft		m		ft		m		ft	
	1	3.3	3	9.8	5	16.4	7	23.0	10	32.8		
Photometrics	lux	fc	lux	fc	lux	fc	lux	fc	lux	fc		
FULL ON	16,450	1,528	2,200	204	900	84	565	52	274	25		

**DIMENSIONAL DIAGRAM**



**OPTIONAL ACCESSORIES**

ORDER CODE	ITEM
TRIGGER CLAMP	Heavy Duty Wrap Around Hook Style Clamp
EWDMSYSTEM	Wireless DMX System (1 Transmitter, 1 Receiver)
EWDMXT	Wireless DMX Transmitter
EWDMXR	Wireless DMX Receiver
AC3PDMX5PRO	5 ft. (1.5m) 3pin PRO DMX Cable
AC5PDMX5PRO	5 ft. (3m) 5pin PRO DMX Cable
PLC3	3' (1m) PowerCON PRO Link Cable
PLC6	6' (1.8m) PowerCON PRO Link Cable
	Additional Cable Lengths Available



Specifications are subject to change without notice ©Elation Professional

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040  
323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, Netherlands  
+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu