





SKM 935

RF Wireless Systems | evolution wireless 

Cat. No. 021636

General Description


A truly professional stage microphone, the cardioid SKM 935  hand-held transmitter easily cuts through the mix, offering clarity and projection even with high ambient sound levels. It can be combined with any of the receivers from the ew 500  Series or the EM 550 . The SKM 935  features nine frequency banks with up to 20 directly accessible presets each – ready for immediate use.



Technical Data

RF frequency range	518–866 MHz
Transmission frequencies	1,440
Presets	max. 20
Switching bandwidth	36 MHz
Peak deviation	± 48 kHz
Compander	HDX
AF frequency response	40–18,000 Hz
Signal-to-noise ratio	> 115 dB(A)
THD	< 0.9 %
In compliance with	ETS 300422, ETS 300445, CE , FCC
Power supply	2 x 1.5 V (AA)
RF output power	30 mW
Operating time	> 8 hrs
Dimensions	d = 50 mm, l = 225 mm
Weight	450 g
Transducer	dynamic
Sensitivity	2 mV/Pa
Max. SPL	154 dB
Pick-up pattern	cardioid






Features

- Absolutely reliable transmission and extended range due to high RF output power
- Pilot tone squelch for eliminating RF interference
- Rugged metal housing
- Backlit display (lights up when a button is pushed)
- User-friendly menu operation
- Lock function avoids accidental changing of settings
- HDX compander for crystal-clear sound
- 4-step battery status display, also transmitted to receiver
- Mute function
- Wide range of accessories adapts the hand-held transmitter to any requirement
- Delivery includes: 1 SKM 935  hand-held transmitter (dynamic, cardioid)
 - 1 MZQ 1 microphone clip
 - 1 protective pouch
 - 2 batteries

Recommended Accessories

■ CC 2 system case	Cat. No. 009826
■ MZW 1 foam windshield, anthracite	Cat. No. 004839
■ BA 2015 accu pack	Cat. No. 009950
■ L 2015 charging unit	Cat. No. 009828

Product Variants

■ SKM 565  -A: Frequency range 518–554 MHz	Cat. No. 009777
■ SKM 565  -B: Frequency range 626–662 MHz	Cat. No. 009778
■ SKM 565  -C: Frequency range 740–776 MHz	Cat. No. 009779
■ SKM 565  -D: Frequency range 786–822 MHz	Cat. No. 009780
■ SKM 565  -E: Frequency range 830–866 MHz	Cat. No. 009781