

# Product Bulletin

# Sub 8



## Description:

The Sub8 is a small yet powerful subwoofer designed to extend the low frequency capabilities of any nearfield monitoring system. The Sub8 houses an excellent 8" woofer with a large 50 mm voicecoil, and is driven by a 160 W ICE Power amp. This amp stays cool while handling maximum power levels even if they are sustained.

The front baffle features two motorized knobs that let you tailor input level and crossover frequency settings for the best performance in your studio. These knobs can be controlled with an included wireless remote, allowing you to optimize your sound reproduction from your ideal listening position.

The Sub8 is an ideal match for ADAM monitors such as the ANF10, P11A, S1A and S2A. In addition to a traditional black model, ADAM will also offer a silver version that will be a perfect complement to the Artist desktop monitor.



Technical data	Sub8
Driver	215 mm (8")
Free air resonance	28 Hz
Voice coil ø	50 mm
Cone material	coated paper
Built in amps	160 W/240 W
Frequ. response ±3dB	28 Hz-150 Hz
THD >80Hz	≤1 %
SPL max in 1m	112 dB SPL
Crossover frequ. (telecommander)	50 - 150 Hz
Frequ. response sat. (switchable)	85 Hz
variable Input gain (telecommander)	-40 - +12 dB
Phase switch	0° / 180°
In- and outputs	balanced XLR + unbalanced RCA
Input impedance	10 kΩ
Weight	12 kg
Magnetical shielding	no
Width x Height x Depth	26x41x38 cm
Warranty	2 years

### ADAM Audio GmbH

Lobeckstr. 36 | 10969 Berlin-Germany  
phone: +49 30-863 00 97-0  
fax: +49 30-863 00 97-7  
email: info@adam-audio.com  
web: [www.adam-audio.com](http://www.adam-audio.com)

### ADAM USA

3717 E. Thousand Oaks Blvd.  
Suite 215 | Westlake Village | CA, 91362  
phone: +1 805-413 11 33  
fax: +1-805-413 11 34  
email: usa@adam-audio.com

### ADAM Audio Asia Pte. Ltd.

51, Changi Business Park Central 2  
#08-03, The Signature | Singapore 486066  
phone: +65-67 25 81 81  
fax: +65-67 25 81 82  
email: asia@adam-audio.com