

Transparent microphone cable



Applications:
Professional balanced microphone audio cable for Broadcast, suitable for fixed installation on long distances.

Characteristics:
Conductors: n. 1 O.F.C. red copper
n. 1 O.F.C. tinned copper

Cond. Insulation: Compact PE
Core colours: Transparent
Inner sheath between cores and shield: Braided covering 95%
Shield: O.F.C. tinned copper

Sheath: PVC
Sheath colour: Transparent



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C196	2	2 x 0,50 (20 AWG)	16x0,20	2,1	7,0	100	B	6,7

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
45	56	95
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70

Special Twinaxial Microphone Cable



Applications:
Special Twinaxial audio cable. Flexible and excellently balanced microphone cable for fixed or mobile installation suitable even for the realization of audio assembly.

Characteristics:
Conductors: O.F.C. red copper
Cond. Insulation: Compact XLPE
Core colours: Red, White
Special inner sheath between cores and shield: Spiral covering 100%

Shield: O.F.C. red copper
Sheath: PVC
Sheath colour: Blue-night



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
TSK 1033	2	2 x 0,22 (24 AWG)	28x0,10	1,2	6,2	100	B	5,0
TSK 1034	2	2 x 0,40 (21 AWG)	48x0,10	1,5	6,7	100	B	6,5

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
90	70	106
56	50	90
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70

Microphone Cable



Applications:
Flexible balanced microphone audio cable for fixed or mobile installation suitable even for the realization of audio assembly.

Characteristics:
Conductors: n. 1 O.F.C. red copper
n. 1 O.F.C. tinned copper

Cond. Insulation: Compact PE
Core colours: Transparent
Waste filler between conductors: Flame Retardant PVC

Shield: CEI 20-22/II°
Sheath: Blue-night



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C112	2	2 x 0,35 (22 AWG)	11x0,20	1,7	6,3	100	B	5,0

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
60	61	104
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70