

Special video cables 75 Ω



Applications:
Special cable composed of 2 mini-coaxial video cables for S-VHS professional systems. Flexible cable for fixed and mobile installation with big external diameter, suitable to connect high quality connectors as for example: **tasker® SP 54** S-VHS Mini-DIN 4 pin.

Characteristics:
Conductors: stranded in O.F.C. red copper
Insulations: PEE
Shields: Spiral covering 100% O.F.C. tinned copper
Inner sheaths: PVC
Sheath colours: Red, White
Total sheath: PVC
Sheath colour: Blue-night



tasker® Code	Cond. number	Cond. number Nominal section	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C139	2	2 x 75 Ω (0,08 mm ²)	10x0,10	1,5	2,8	7,5	100	B	7,0



Applications:
Special multi-video flat cable composed of 3 mini-coaxial video cables for fixed and mobile installation and video assembly, or other R.G.B. video applications.

Characteristics:
Conductors: stranded in O.F.C. red copper
Insulations: PE
Shields: Braided covering 90% O.F.C. silver plated copper
Inner sheaths: PVC
Sheath colours: Red, Green, Blue
Sheath: Flame Retardant PVC CEI 20-22/II°
Sheath colour: Black



tasker® Code	Cond. number	Cond. number Nominal section	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
TSK 1083	3	3 x 75 Ω (0,08 mm ²)	9x0,10	1,5	2,8	4,2x10,2	100	B	6,5

Conductor Resistance		Capacity Core/core		Capacity Core/shield	
Ω/Km ± 5%		pF/mt		pF/mt	
210				67	
Velocity of propagation %	Impedance Ω ± 3%	Max rated Voltage V	Operative Temperature °C		
66	75	49	-15 / +70		
Attenuation db/100mt					
50 MHz	100 MHz	200 MHz	400 MHz	800 MHz	1000 MHz
19,2	27,9	40,7	59,2	85,3	101,0