

tasker®

Special coaxial video cables 75 Ω

nightly blue®

RoHS
Conformity



Applications:

Extra flex coaxial cable with double shielding, aluminium tape and braided red copper covering 100%.
Cable for fixed and mobile application, suitable for the realization of video and audio cable assembly.
Cable for High definition TV or for digital audio transmission according to AES/EBU standards.

Characteristics:

Conductor: stranded in O.F.C. red copper
Insulation: PEE
I° Shield: Aluminium tape covering 100%
II° Shield: Braided covering 90%
O.F.C. red copper
Sheath: PVC
Sheath colour: Black



Conductor Resistance		Capacity Core/core		Capacity Core/shield	
Ω/Km ± 5%		pF/mt		pF/mt	
60				57	
Velocity of propagation %	Impedance Ω ± 3%	Max rated Voltage V		Operative Temperature °C	
66	75	49		-15 / +70	
Attenuation db/100mt					
50 MHz	100 MHz	200 MHz	400 MHz	800 MHz	1000 MHz
8,2	12,5	17,5	24,8	34,8	39,0

RoHS
Conformity

Applications:

Flexible coaxial cable with double shielding, aluminium tape and braided red copper covering 100%.
Cable for fixed and mobile application, suitable for the realization of video and audio cable assembly.
Cable for High definition TV or for digital audio transmission according to the AES/EBU standards.
Professional cable with big external diameter.

Characteristics:

Conductor: stranded in O.F.C. red copper
Insulation: PEE
I° Shield: Aluminium tape covering 100%
II° Shield: Braided covering 90%
O.F.C. red copper
Sheath: PVC
Sheath colour: Blue-night



Conductor Resistance		Capacity Core/core		Capacity Core/shield	
Ω/Km ± 5%		pF/mt		pF/mt	
30				66	
Velocity of propagation %	Impedance Ω ± 3%	Max rated Voltage V	Operative Temperature °C		
66	75	49	-15 / +70		
Attenuation db/100mt					
50 MHz	100 MHz	200 MHz	400 MHz	800 MHz	1000 MHz
7,5	11,5	16,5	23,5	33,5	38,0

tasker® Code	Cond. number	Cond. number Nominal section	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
T 40	1	1 x 75 Ω (0,34 mm²)	30x0,12	3,7		6,1	100	B	4,5

nightly blue®



tasker® Code	Cond. number	Cond. number Nominal section	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C140	1	1 x 75 Ω (0,75 mm²)	80x0,11	4,9		8,0	100	B	7,5