



### Applications:

Flexible cable composed of: 5 mini-coaxial cables for video R.G.B.+H.V. transmission on professional video systems and for Monitors and video-projectors.

Cable for fixed and mobile installation, suitable for the realization of video assembly.

### Characteristics:

Conductors: stranded in O.F.C. red copper  
 Insulations: PEE  
 Shields: spiral covering 100% O.F.C. tinned copper  
 Sheaths: PVC  
 Sheath colours: Red, Green, Blue, Black, White  
 Total Sheath: Flame Retardant PVC CEI 20-22/II°  
 Sheath colour: Grey



tasker® Code	Cond. number	Cond. number Nominal section	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C263	5	5 x 75 Ω (0,08 mm²)	10x0,10	1,6	2,8	9,8	100	B	12,0
							300	B	
							500	B	

Conductor Resistance		Capacity Core/core		Capacity Core/shield	
Ω/Km ± 5%		pF/mt		pF/mt	
210				67	
Velocity of propagation of coax %	Impedance	Max rated Voltage	Operative Temperature		
%	Ω ± 3%	V	°C		
66	75	49	-15 / +70		
Attenuation db/100mt					
50 MHz	100 MHz	200 MHz	400 MHz	800 MHz	1000 MHz
19,5	28,5	41,7	60,2	87,3	103,0



### Applications:

Professional cable composed of: 5 mini-coaxial cables for video R.G.B.+H.V. transmission on professional video systems and for Monitors and video-projectors.

Cable for fixed and mobile installation, suitable for the realization of video assembly.

### Characteristics:

Conductors: stranded in O.F.C. tinned copper  
 Insulations: PPE  
 Shields: Braided covering 90% O.F.C. tinned copper  
 Sheaths: Flame Retardant PVC CEI 20-22/II°  
 Sheath colours: Red, Green, Blue, Black, White  
 Total taping: unweaved Polyester  
 Total Sheath: Flame Retardant PVC CEI 20-22/II°  
 Sheath colour: Black



tasker® Code	Cond. number	Cond. number Nominal section	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C145	5	5 x 75 Ω (0,08 mm²)	7x0,12	1,4	2,4	9,2	100	B	11,5

Conductor Resistance		Capacity Core/core		Capacity Core/shield	
Ω/Km ± 5%		pF/mt		pF/mt	
210				67	
Velocity of propagation of coax %	Impedance	Max rated Voltage	Operative Temperature		
%	Ω ± 3%	V	°C		
66	75	49	-15 / +70		
Attenuation db/100mt					
50 MHz	100 MHz	200 MHz	400 MHz	800 MHz	1000 MHz
19,7	28,7	42,0	61,2	88,5	105,0