

Shielded flat audio cables



Applications:
Divisible shielded flat cable for professional head-phones and for sound reproduction. Suitable for the realization of high quality audio assembly.
Low capacity cable.

Characteristics:

Conductors: n. 1 O.F.C. red copper
n. 1 O.F.C. tinned copper
Cond. Insulation: Compact PE
Core colours: Transparent
Shields: Braided covering 100%
O.F.C. tinned copper
Sheath: PVC
Sheath colours: Red, Blue, Yellow, Green

| tasker® Code | Cond. number | Nominal section mm ² | Cond. Format. mm. | External Core Ø mm. | External Cable Dimension mm. | Reel or Spool (* pag. II) | | |
|-----------------|--------------|------------------------------------|----------------------|------------------------|---------------------------------|------------------------------|------|-----|
| | | | | | | mt. | Type | Kg. |
| C220 | 2 | 2 x 0,25 (23 AWG) | 8x0,20 | 1,6 | 5,0 x 10,3 | 100 | B | 6,0 |



Applications:
Divisible shielded flat audio cable with central copper wire. Suitable for the realization of high quality audio and Hi-Fi car assembly.
Low capacity cable.

Characteristics:

Conductors: O.F.C. red copper
Cond. Insulation: Foam PE
Core colours: Red, White
Shields: Braided covering 100%
O.F.C. red copper
Sheath: PVC
Sheath colour: Transparent

| tasker® Code | Cond. number | Nominal section mm ² | Cond. Format. mm. | External Core Ø mm. | External Cable Dimension mm. | Reel or Spool (* pag. II) | | |
|-----------------|--------------|------------------------------------|----------------------|------------------------|---------------------------------|------------------------------|------|-----|
| | | | | | | mt. | Type | Kg. |
| C204 | 2 +1 | 2 x 0,35 +1 x 0,35 (22 AWG) | 45x0,10 45x0,10 | 3,1 | 5,5 x 13,0 | 50 | B | 4,0 |

| Conductor Resistance | Capacity Core/core | Capacity Core/shield |
|----------------------|--------------------------|--------------------------|
| Ω/Km ± 5% | pF/mt | pF/mt |
| 75 | 42 | 130 |
| | Max rated Voltage AC - V | Operative Temperature °C |
| | 49 | -15 / +70 |

Notes: