



**Applications:**  
Multipair cables with separate shielded and insulated pairs.  
Extra flex cables for the realization of audio balanced multi-taps.

**Characteristics:**  
**Conductors:** O.F.C. tinned copper  
**Cond. Insulation:** PVC  
**Pair colours:** White-Brown, White-Blue, White-Black, White-Red, White-Yellow, White-Grey, White-Orange, White-Green, White-Violet, White-Pink, White-Light Blue, White-Light Brown  
**Pair Shields:** Spiral covering 100% O.F.C. tinned copper PVC  
**Inner sheath:** PVC  
**Insulat. colours:** Brown, Blue, Black, Red, Yellow, Grey, Orange, Green, Violet, Pink, Light blue, Light Brown  
**Total Sheath:** PVC  
**Sheath colour:** Black



tasker® Code	Cond. number	Nominal section mm <sup>2</sup>	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C272	2x2	2 x 2 x 0,08 (28 AWG)	12x0,10	0,9	2,9	8,0	100	B	7,5
C274	4x2	4 x 2 x 0,08 (28 AWG)	12x0,10	0,9	2,9	9,2	100	B	11,5
C278	8x2	8 x 2 x 0,08 (28 AWG)	12x0,10	0,9	2,9	12,2	100	B	18,5
C264	12x2	12 x 2 x 0,08 (28 AWG)	12x0,10	0,9	2,9	15,0	50	B	13,5

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
210	170	200
210	170	200
210	170	200
210	170	200
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70

Notes: