

Applications:
Special DMX cables composed of:
-n° 2 Digital audio cables 110 Ω (A)
-n° 1 Power cable (B)

Characteristics:

A) Conductors: O.F.C. tinned copper
Cond. Insulation: PPE
Core colours: Red, Blue
Textile fillers between conductors
Drain wire: O.F.C. tinned copper
Total taping in unweaved polyester
Shields: Spiral covering 100%
O.F.C. red copper
Inner Sheath: Flame Retardant PVC
B) Conductors: O.F.C. red copper
Cond. Insulation: Flame Retardant PVC
Core colours: Brown, Blue, Yellow/green
Inner Sheaths: Flame Retardant PVC
Waste filler and PVC among elements
Total taping in unweaved polyester
Total Sheath: Flame Retardant PVC
CEI 20-22/II°
Sheath colour: Black



****C290: Production on demand**



tasker® Code	Cond. number	Nominal section mm²	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C284	2x2	2 x 2 x 0,22 (24 AWG)	28x0,10	1,5	4,0	13,8	100	B	28,0
	+3	3 x 1,50 (16 AWG)	48x0,20	3,0	7,2	15,5	100	B	
C290**	2x2	2 x 2 x 0,22 (24 AWG)	28x0,10	1,5	4,0	13,8	100	B	28,0
	+3	3 x 2,50 (13 AWG)	50x0,25	3,4	8,1	15,5	100	B	

DMX CABLE
2 Digital Audio + Power
suitable for Active Loudspeakers

Conductor Resistance	Capacity Core/core	Capacity Core/shield
Ω/Km ± 5%	pF/mt	pF/mt
90	50	95
16		
90	50	95
12		
Impedance	Max rated Voltage AC - V	Operative Temperature °C
110	49	-15 / +70

Notes: