



Applications:
S.-F.T.P. Shielded Foiled Twisted Pairs cable cat. 5e UL/ETL verified for Local Area Network – LAN cables, for assembled cables or mobile installations.

For **RJ 45 8 Pin shielded** connectors
Standards: **EIA/TIA 568.**

Characteristics:

- Conductors: **stranded in O.F.C. red copper**
- Cond. insulation: **PE**
- Pair colours: **White/blue-Blue, White/orange-Orange, White/green-Green, White/brown-Brown**
- I° Shield: **Aluminium tape covering 100%**
- Drain wire: **stranded in tinned copper**
- II° Shield: **Braided covering 70% O.F.C. tinned copper**
- External Sheath: **PVC**
- Sheath colour: **Blue-night**



tasker® Code	Cond. number	Nominal section AWG	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C701	4x2	4 x 2 x 26 (0,14 mm²)	7x0,15	0,9		7,0	100	B	6,0
							500	B	

Conductor Resistance $\Omega/\text{Km} \pm 5\%$	Impedance $\Omega \pm 5\%$ $1 \div 100 \text{ MHz}$	Max Rated Voltage AC - V
140	100	49
		Operative Temperature °C
		-15 / +70

Notes: