



**Applications:**  
Professional multipair digital audio cable 110 Ω AES/EBU for direction equipments and digital mixers and/or for the realization of assembled cables and professional multisockets.

**Characteristics:**  
 Conductors: O.F.C. tinned copper  
 Cond. Insulation: PPE  
 Pair colours: Red, Blue  
 Drain wire: O.F.C. tinned copper  
 Shields: Spiral covering 100%  
 O.F.C. red copper  
 Inner Sheaths: Flame Retardant  
 PVC CEI 20-22/II°  
 Ins. colours: White, Black, Green, Yellow, Blue, Red, Grey, Pink, Violet, Orange, Light-Blue, Brown  
 Textile fillers among pairs  
 Total taping in unweaved polyester  
 Sheath: Flame Retardant  
 PVC CEI 20-22/II°  
 Sheath colour: Black



tasker® Code	Cond. number	Nominal section AWG	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C804	4x2	4 x 2 x 24 (0,22 mm <sup>2</sup> )	28x0,10	1,5	4,0	12,3	100	B	20,0
C808	8x2	8 x 2 x 24 (0,22 mm <sup>2</sup> )	28x0,10	1,5	4,0	16,3	100	B	30,0
C812	12x2	12 x 2 x 24 (0,22 mm <sup>2</sup> )	28x0,10	1,5	4,0	19,3	100	B	50,0

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
90	50	95
90	50	95
90	50	95
Impedance Ω	Max rated Voltage AC - V	Operative Temperature °C
110	49	-15 / +70

Notes: