

CSR Lamps

The GE CSR1200/2/SE lamp is a single ended metal halide lamp with an outer jacket . It's small arc gap of 10 mm provides greater optical control and luminance. This lamp is compact, highly efficient, and at 7200K provides a white bright light. It is a cold start lamp with a maximum seal temperature of 350° C . The CSR1200/2/SE is mainly used in event lighting.

Product Description CSR1200/2/SE

CSR1200/2/SE
49490
6
1200
100 <u>+</u> 15V
13.8A
5
110,000 Lm
92
>75
× 0.305
y 0.315
7200K
10 ± 1.0 mm
MAX175
85±1.0
40 MAX
800hr
G22


Lamp Operation

Burn Position Any Maximum Seal Temperature 350° C Cooling Forced Cooling/Fan Lamp can be used on electronic or AC magnetic Ballast/igniters

Application Information

- Do not exceed rated wattage or voltage
- •Replace lamp at or before rated life
- •Do not exceed rated seal temperature
- Use only with properly rated fixtures and ballasts





GE Consumer is industrial specialty Lighting is constantly developing and improving its products. For this reason, all product descriptions in this bruchure or intended as a general guide, and we may change specializations from the time in the interest of product development, which they refer and shall not form part of any controct. Data in this guide has been obtained in controlled experimental conditions. However, GE Lighting cannot accept only liability or insign from the relaince on such data to the extent permitted by low.

MAX \$40

| GE | 100 | 2/SE | 12 0 0 W | MIE | JAMA|

^{*}ECG = electronic control gear/ MCG = Magnetic control gear