

Extra-flex speaker cables



Applications:

Extra flexible round cables for loudspeakers and Hi-Fi Car systems, suitable for the realization of professional flexible audio assembly with speakon, banana and other audio connectors.

Cable with conductors composed of extremely thin elementary wires (from n° 189 to n° 511 of Ø mm. 0,10) that are first bound up in beams and then stranded for a better transmission of the audio signal.

Characteristics:

Conductors: O.F.C. red copper
 Cond. Insulation: Compact PE
 Core colours: White, Red
 Waste filler between conductors
 Total taping in unweaved polyester
 Sheath: PVC
 Sheath colour: Blue-night



tasker® Code	Cond. number	Nominal section mm²	Cond. Format. mm.	External core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
TSK 1020	2	2 x 1,50 (16 AWG)	27x7x0,10	2,5	7,5	100	B	7,0
TSK 1021		2 x 2,50 (13 AWG)	45x7x0,10	3,5	9,0	100	B	11,5
TSK 1024		2 x 4,00 (11 AWG)	73x7x0,10	4,0	10,5	50	B	9,0

Notes:

Conductor Resistance	Max rated Voltage	Operative Temperature
Ω/Km ± 5%	AC - V	°C
18	49	-15 / +70
12	49	-15 / +70
6	49	-15 / +70