

Microphone cables



Applications:
Microphone cables for sound reproduction.

Characteristics:
 Conductors: O.F.C. red copper
 Cond. Insulation: Compact PE
 Core colours: White, Yellow, Red, Green
 Waste filler between conductors
 Shield: Braided covering 60%
 O.F.C. red copper
 Sheath: PVC
 Sheath colour: Black



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C255	2	2 x 0,22 (24 AWG)	7x0,20	1,2	5,0	100	B	3,0
C256	3	3 x 0,22 (24 AWG)	7x0,20	1,2	5,2	100	B	3,5
C257	4	4 x 0,22 (24 AWG)	7x0,20	1,2	5,5	100	B	4,0

nightly blue®



Applications:
Special flat pair cable, more flexible and divisible, suitable for the realization of professional audio-balanced assembly.

Characteristics:
 Conductors: O.F.C. red copper
 Cond. Insulation: Compact XLPE
 Pair colours: White-Red, White-Blue
 Drain wire: O.F.C. tinned copper
 Shield: Spiral covering 100%
 O.F.C. red copper
 Sheath: PVC
 Sheath colour: Blue-night

Professional Flat Audio Cable



TSK 1042	2x2	2 x 2 x 0,22 (24 AWG)	28x0,10	1,1	4,5 x 9,1	100	B	6,0
----------	-----	-----------------------	---------	-----	-----------	-----	---	-----

Flat divisible pair balanced microphone cable

nightly blue®



Applications:
Flexible pair audio QUAD cable for sound reproduction.

Characteristics:
 Conductors: O.F.C. red copper
 Cond. Insulation: Compact XLPE
 Pair colours: Transparent-Red, Transparent-Yellow
 Total taping in unwaxed polyester
 Drain wire: O.F.C. tinned copper
 Shield: Braided covering 95%
 O.F.C. tinned copper
 Sheath: PVC
 Sheath colour: Blue-night

Audio Quad cable



TSK 1044	2x2	2 x 2 x 0,22 (24 AWG)	28x0,10	1,1	5,2	100	B	4,0
----------	-----	-----------------------	---------	-----	-----	-----	---	-----

Audio Quad cable



Applications:
Flexible pair audio QUAD cable for sound reproduction.

Characteristics:
 Conductors: O.F.C. red copper
 Cond. Insulation: Compact XLPE
 Pair colours: Transparent-Red, Transparent-Yellow
 Total taping in unwaxed polyester
 Drain wire: O.F.C. tinned copper
 Shield: Braided covering 95%
 O.F.C. tinned copper
 Sheath: PVC
 Sheath colour: Blue-night