

## DMX cables



**Applications:**  
Special DMX cable with small diameter composed of:  
-n° 1 Digital audio cable 110 Ω (A)  
-n° 3 Power conductors (B)

**Characteristics:**  
**A) Conductors:** O.F.C. tinned copper  
**Cond. Insulation:** PPE  
**Core colours:** Red, Blue  
**Textile fillers between conductors**  
**Drain wire:** O.F.C. tinned copper  
**Total taping in unweaved polyester**  
**Shield:** Spiral covering 100% O.F.C. red copper  
**Inner Sheath:** Flame Retardant PVC  
**B) Conductors:** O.F.C. red copper  
**Cond. Insulation:** Flame Retardant PVC  
**Core colours:** Brown, Blue, Yellow/green  
**Waste filler among elements**  
**Total taping in unweaved polyester**  
**Total Sheath:** Flame Retardant PVC CEI 20-22/II°  
**Sheath colour:** Black



tasker® Code	Cond. number	Nominal section mm²	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
TSK 1048	1x2	1 x 2 x 0,22 (24 AWG)	28x0,10	1,5	4,0	9,0	100	B	10,5
	+3	3 x 0,75 (18 AWG)	24x0,20	2,1					

DMX CABLE  
1 Digital Audio + Power  
suitable for Active Loudspeakers

Conductor Resistance	Capacity Core/core	Capacity Core/shield
Ω/Km ± 5%	pF/mt	pF/mt
90	50	95
32		
Impedance	Max rated Voltage AC - V	Operative Temperature °C
Ω		
110	49	-15 / +70



**Applications:**  
Special DMX cable composed of:  
-n° 1 Digital audio cable 110 Ω (A)  
-n° 1 Power cable (B)

**Characteristics:**  
**A) Conductors:** O.F.C. tinned copper  
**Cond. Insulation:** PPE  
**Core colours:** Red, Blue  
**Textile fillers between conductors**  
**Drain wire:** O.F.C. tinned copper  
**Total taping in unweaved polyester**  
**Shield:** Spiral covering 100% O.F.C. red copper  
**Inner Sheath:** Flame Retardant PVC  
**B) Conductors:** O.F.C. red copper  
**Cond. Insulation:** Flame Retardant PVC  
**Core colours:** Brown, Blue, Yellow/green  
**Inner Sheath:** Flame Retardant PVC  
**Waste filler and PVC between elements**  
**Total taping in unweaved polyester**  
**Total Sheath:** Flame Retardant PVC CEI 20-22/II°  
**Sheath colour:** Black



tasker® Code	Cond. number	Nominal section mm²	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C283	1x2	1 x 2 x 0,22 (24 AWG)	28x0,10	1,5	4,0	13,8	100	B	27,5
	+3	3 x 1,50 (16 AWG)	48x0,20	3,0	7,2				

DMX CABLE  
1 Digital Audio + Power  
suitable for Active Loudspeakers

Conductor Resistance	Capacity Core/core	Capacity Core/shield
Ω/Km ± 5%	pF/mt	pF/mt
90	50	95
16		
Impedance	Max rated Voltage AC - V	Operative Temperature °C
Ω		
110	49	-15 / +70