



SWITZERLAND

Audio Bauer Pro AG
Bernstrasse-Nord 182, CH-8064 Zürich, Switzerland
Phone: +41 44 432 32 30, Fax: +41 44 432 65 58
Web: www.voicetechnologies.net
Email: info@audio-bauerpro.ch

VT800 Lightweight Headworn Cardioid



VT800 Lightweight Headworn Cardioid

The VT800 features a tight cardioid pattern and frequency response engineered to meet most voice applications.

Much consideration has been put into the physical design of the VT800. The flexible boom arm enables the user to position the microphone for optimum sound and gain before feedback. Cable runs neatly to the back of neck for best concealment. The head-band is highly resistant to corrosion and is easy to clean.

VT800 Standard Specifications (Preliminary)

Microphone:

Generating Element:

Polar Pattern:

Frequency Response:

Sensitivity (@ 1kHz):

Maximum Input SPL:

Noise Level:

Dynamic Range:

Signal Noise Ratio:

Bias:

Impedance:

Cable:

Weight:

Color:

Standard Accessory:

Wiring Configuration (3-wire):

Electret Condenser

Cardioid

50Hz- 18 kHz

-53dB re 1V/Pascal (2.3mV/Pa)

120dB based on 9V supply

32dB "A" Weighted

88dB *

62dB @94dB SPL

1.5V to 9V

2.8 to 6.8 kOhms, nominal 4.4 kOhms

Length 1,5m

18 grams (without cable/connector)

beige or black


Microphone Windscreen

red: "+"

clear: signal

shield: ground

Frequency Response



VT800 Lightweight Headworn Cardioid - No accessories available yet.

